







Circular table saw MS550 / MS700

The saw for compound mitre cutting

Circular table saw MS550

The saw for compound mitre cutting

DESCRIPTION:

- robust machine with high precision accuracy
- all controlling and adjusting units are positioned in the front side of the machine
- variable adjustable hydro pneumatic saw feed
- saw blade inclination from 90° to 45° to the right, over handwheel adjustment on the front side of the machine, variable adjustable to scale or digital readout (on request: PE 600)
- rotation of the table with saw unit from 90° to 20° to the left and from 90° to 20° to the right. Angle positioning for 45° - 90° - 45° with adjustable index stops. Intermediate angle adjustment with scale or digital readout (upon request)
- angular positioning for 45°-90°-45° with adjustable index-stop
- · easy rotation and inclination through precise bearings
- saw blade dia. 550mm giving large cutting capacity
- two vertical clamping cylinders from the top adjustable to suit material
- material clamping pressure monitoring; saw feed only under full air pressure
- selection switch for adjustment of machine by idle running saw blade (clamp)
- cover guard manually closing / opening
- mobile operating panel
- profile clamping pressure regulator
- · air service and maintenance unit

TECHNICAL DATA:

Voltage:	400V, 50Hz
Power:	2,2 kW
Revolutions:	2300 R/min
Saw blade:	Ø 550 mm
Air connection:	6-8 bar
Dimensions:	1400 x 2200 x 1800 mm
Weight:	1040 kg

DETAILS / OPTIONS:



Details MS550

ORDER NUMBERS:

95074794	Underfloor saw MS550

Optionen:

95074796 Additional charge motor power 4KW for MS55085000381 Digital display for pivoting

Underfloorsaw MS700

The saw with big 700mm saw blade for compound mitre cutting

DESCRIPTION:

- hydropneumatic stepless saw feed
- saw blade tilt 90°-45° right
- pneumatic angle positioning
- table rotation with saw aggregat from $90^\circ\mathchar`e\screte{-}22,5^\circ$ left and right
- 4 kW motor
- Intermediate angle adjustment with scale
- HM saw blade 700 mm

TECHNICAL DATA:	
Voltage:	230/400V, 50/60Hz
Power:	4 kW
Saw blade:	Ø 700 mm
Air connection:	6-8 bar
Weight:	820 kg



ORDER NUMBERS:

766035000000 Underfloor saw MS700

WEGOMA GmbH Bahnhofstr. 7 75399 Unterreichenbach Telefon: +49 (7235) 973 93-0 Telefax: +49 (7235) 973 93-200 info@wegoma.de